



Safety Data Sheet Sections

SECTION 1: IDENTIFICATION	2
SECTION 2: HAZARD IDENTIFICATION.....	2
PRECAUTIONARY STATEMENTS	2
SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.....	3
SECTION 4: FIRST-AID MEASURES.....	3
SECTION 5: FIRE-FIGHTING MEASURES.....	4
SECTION 6: ACCIDENTAL RELEASE MEASURES	5
SECTION 7: HANDLING AND STORAGE	5
SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION	5
EXPOSURE LIMITS:	5
INDIVIDUAL PROTECTION MEASURES / PERSONAL PROTECTIVE EQUIPMENT.....	5
SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES	5
SECTION 10: STABILITY AND REACTIVITY.....	6
SECTION 11: TOXICOLOGICAL INFORMATION	7
SECTION 12: ECOLOGICAL INFORMATION.....	7
SECTION 13: DISPOSAL CONSIDERATIONS.....	7
SECTION 14: TRANSPORT INFORMATION.....	7
SECTION 15: REGULATORY INFORMATION.....	8
SECTION 16: OTHER INFORMATION	8
ACRONYM LIST	8

PREPARED BY:


Regulatory Division
Project Clean Inc.
(formerly Maxim Chemical International Inc.)

LAST UPDATE:

2020-05-15

SECTION 1: IDENTIFICATION	
Product Trade Name:	Maxim #1 Remover
Product Code:	1300531
Recommended Use:	Maximum performance stripper
Restrictions on Use:	For Industrial and Institutional use only
Manufacturer Name:	Project Clean Inc.
Manufacturer Address:	1607 Derwent Way, Delta, B.C. Canada V3M 6K8
Manufacturer Phone Number:	800-663-9925
Email Address of Competent Person Responsible for the SDS:	regulatory@projectclean.com
Emergency Phone Number/ 24-Hour Number:	For Transportation Emergencies: Canutec 613-996-6666 Emergency Response Services: Chemtrec 800-424-9300

[Back to Top](#)

SECTION 2: HAZARD IDENTIFICATION	
Physical Hazards:	CORROSIVE TO METALS – Category 1
Health Hazards:	SKIN CORROSION/IRRITATION – Category 1
	EYE DAMAGE/IRRITATION – Category 1
	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) – Category 3
Symbol:	
Signal word:	DANGER
Hazard Statement:	H290 May be corrosive to metals.
	H314 Causes severe skin burns and eye damage.
	H318 Causes serious eye damage.
	H335 May cause respiratory irritation.
PRECAUTIONARY STATEMENTS	
Prevention:	P234 Keep only in original packaging.
	P260 Do not breathe dusts or mists.
	P264 Wash hands or affected area thoroughly after handling.
	P280 Wear protective gloves/protective clothing/eye protection/face protection.
	P271 Use only outdoors or in a well-ventilated area.

PREPARED BY:

Regulatory Division
 Project Clean Inc.
 (formerly Maxim Chemical International Inc.)

LAST UPDATE:

2020-05-15

SECTION 2: HAZARD IDENTIFICATION	
Responses:	P390 Absorb spillage to prevent material-damage.
	P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
	P302 + P361 + P354 IF ON SKIN: Take off immediately all contaminated clothing. Immediately rinse with water for several minutes.
	P363 Wash contaminated clothing before reuse.
	P304 + P340 + P316 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get emergency medical help immediately.
	P321 Specific treatment (see supplemental first aid information on this label).
	P305 + P354 + P338 + P317 IF IN EYES: Immediately rinse with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical help.
Storage:	P405 Store locked up.
	P406 Store in a corrosion resistant container with a resistant inner liner.
	P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
Disposal:	P501 Dispose of contents/ container to an approved waste disposal plant.

[Back to Top](#)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS		
Ingredient	Approx. Wt.%	CAS Number
Sodium Metasilicate	1-5	6834-92-0
Sodium Hydroxide	1-5	1310-73-2
Monoethanolamine	1-5	141-43-5
Sodium (C14-16) Olefin Sulfonate	1-5	68439-57-6

[Back to Top](#)

SECTION 4: FIRST-AID MEASURES	
General Information:	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.
Inhalation:	Immediately remove the affected victim to fresh air. If symptoms persist, obtain medical attention. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTER or doctor/physician if feeling unwell.

SECTION 4: FIRST-AID MEASURES	
Skin Contact:	Take off all contaminated clothing immediately. Rinse skin with water/shower. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse.
Eye Contact:	Immediately flush with warm running water for at least 15 minutes, holding eyelids open during flushing. Remove contact lenses, if present and easy to do. If irritation persists, repeat flushing and obtain medical attention immediately.
Ingestion:	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Self-Protection of the First Aider:	Remove all sources of ignition. Ensure that first aid personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.
Most Important Symptoms/ Effects, Acute and Delayed:	<p>Ingestion: Small amounts swallowed incidental to normal handling operations are not likely to cause injury. May burn mouth and throat. May cause gastrointestinal irritation or ulceration.</p> <p>Inhalation: Low toxicity. Excessive exposure may cause severe irritation to the upper respiratory tract.</p> <p>Eyes and skin: May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Brief contact may cause skin burns.</p>
If irritation occurs or persists, get medical attention.	

[Back to Top](#)

SECTION 5: FIRE-FIGHTING MEASURES	
Suitable Extinguishing Media:	Water fog, alcohol foam, dry chemical.
Unsuitable Extinguishing Media:	Direct water stream.
Flammability:	Not flammable.
Flash Point:	Not flammable.
Special Firefighting Procedures:	Wear NIOSH/MSHA approved, self-contained breathing apparatus for firefighting situation. Use water spray to cool all nearby fire exposed surfaces.
Unusual Fire / Explosion Hazards:	Flammable hydrogen may be generated from contact with metals such as aluminum. Avoid contact with nitrites, strong acids, halogenated hydrocarbons.
Hazardous Decomposition Products:	Hydrogen, ammonia, aldehydes, ketones, organic acids.

[Back to Top](#)

SECTION 6: ACCIDENTAL RELEASE MEASURES

Environmental Protection Precautions:	Do not release to the environment or water source.
Steps to be Taken in Case Material is Released or Spilled:	Wear protective equipment. Soak up spills with absorbents, then dispose of in an appropriate waste container. Keep material away from sewers. Reuse if possible. Otherwise dispose recovered material in accordance with all local, Provincial or Federal regulations.

[Back to Top](#)**SECTION 7: HANDLING AND STORAGE**

Precautions to be Taken in Handling and Storage:	Use good industrial hygiene. Do not get in eyes. Avoid contact with skin and clothing. Avoid breathing sprays or mists. Store in a cool, dry place away from incompatibles. Keep container closed when not in use. Do not mix with any other chemicals. Store at temperatures below 30oC and keep from freezing. Do not store in aluminum, copper, copper alloys and galvanized containers.
---	---

[Back to Top](#)**SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION****EXPOSURE LIMITS:**

OSHA (PEL): N/A	ACGIH TLV: N/A	Other exposure limit: N/A
-----------------	----------------	---------------------------

INDIVIDUAL PROTECTION MEASURES / PERSONAL PROTECTIVE EQUIPMENT

Appropriate Engineering Controls:	Mechanical or good general ventilation.
Skin Protection:	Butyl rubber, neoprene, latex or nitrile gloves. Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Appropriate footwear should be selected based on the task being performed and the risks involved.
Eye and Face Protection:	Safety glasses or chemical goggles. Face shield if splashing hazard exists.
Respiratory Protection:	Good general ventilation or local exhaust ventilation for spraying and misting in confined areas.
Other Protective Equipment:	Eye wash, safety shower and full protective clothing recommended in the immediate work area. Rubber boots.

[Back to Top](#)**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Appearance:	Clear, colourless liquid.
--------------------	---------------------------

PREPARED BY:

Regulatory Division
Project Clean Inc.
(formerly Maxim Chemical International Inc.)

LAST UPDATE:

2020-05-15

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES	
Odour:	Mild odor.
Odour threshold:	N/A
pH:	12.0 – 13.0
Melting point/Freezing point:	N/A
Initial boiling point and boiling range:	N/A
Flash Point:	> 100°C
Evaporation Rate (Water=1):	N/A
Flammability:	Not flammable
Upper/Lower flammability or explosive limits:	None
Vapour pressure:	N/A
Vapour density:	N/A
Relative density/Specific gravity (Water = 1):	1.06 @ 20 °C
Solubility(ies):	Soluble in water
Partition coefficient: n-octanol/water:	N/A
Auto-ignition temperature:	Not flammable
Decomposition temperature:	N/A
Viscosity:	N/A
VOCs:	N/A

[Back to Top](#)

SECTION 10: STABILITY AND REACTIVITY	
Reactivity:	N/A
Chemical stability:	Stable under normal storage conditions.
Possibility of hazardous reactions:	Avoid contact with acid/oxidizers.
Conditions to avoid:	Temperatures above 30°C and below 5°C. Avoid contact with incompatible materials.
Incompatibility:	Metals such as aluminum, brass, copper. Nitrites, strong acids, halogenated hydrocarbons.
Hazardous Decomposition Products:	Hydrogen, ammonia, aldehydes, ketones, organic acids.

[Back to Top](#)

PREPARED BY:

Regulatory Division
Project Clean Inc.
(formerly Maxim Chemical International Inc.)

LAST UPDATE:

2020-05-15

SECTION 11: TOXICOLOGICAL INFORMATION

Likely routes of exposure:	Ingestion, skin and eye contact.
Symptoms:	Corrosive to eyes and skin.
Acute Toxicity Estimates:	LD ₅₀ Oral ATE > 2000 mg/kg
	LD ₅₀ Dermal ATE > 2000 mg/kg
	LD ₅₀ Inhalation ATE: N/A
Skin Sensitization:	Data available on components indicates no potential skin sensitization.
Germinal Cell Mutagenicity:	Data available on components indicates no potential germinal cell mutagenicity.
Reproductive Toxicity:	Data available on components indicates no potential reproductive toxicity.
Carcinogenicity:	This product contains <0.03% Diethanolamine (CAS# 111-42-2) which is listed as Group 2B carcinogen by IARC.
Aspiration Hazard:	Data available on components indicates no potential aspiration hazard.

[Back to Top](#)

SECTION 12: ECOLOGICAL INFORMATION

Toxicity to Fresh Water Algae:	N/A
Toxicity to Fish Species:	Sodium Metasilicate (CAS# 6834-92-0): LC ₅₀ (Brachydanio rerio) 210 mg/L, Exposure Time: 96h, Test Type: semi-static
Toxicity to Aquatic Invertebrates:	N/A
Persistence and degradability:	N/A

[Back to Top](#)

SECTION 13: DISPOSAL CONSIDERATIONS

Recommended Waste Disposal Methods:	Reuse if possible. Otherwise dispose recovered material in accordance with all local, Provincial or Federal regulations.
--	--

[Back to Top](#)

SECTION 14: TRANSPORT INFORMATION

Canadian TDG UN Number:	1760
UN Proper Shipping Name:	CORROSIVE LIQUID, N.O.S. (ethanolamine)
Transport Hazard Class(es):	8
Packing Group:	II
Environmental Hazards:	Not available.

PREPARED BY:

Regulatory Division

Project Clean Inc.

(formerly Maxim Chemical International Inc.)

Page 7 of 9

LAST UPDATE:


2020-05-15

SECTION 14: TRANSPORT INFORMATION

Special Precautions for User:	Not available.
Additional Information:	Not available.

[Back to Top](#)

SECTION 15: REGULATORY INFORMATION

<p>HAZARD RATING INFORMATION</p> <p>4 = Extreme 3 = High 2 = Moderate 1 = Slight 0 = Insignificant</p>	<p style="text-align: center;">HMIS</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td style="background-color: #0070C0; color: white; text-align: center;">3</td> <td style="background-color: #0070C0; color: white;">Health</td> </tr> <tr> <td style="background-color: #FF0000; color: white; text-align: center;">0</td> <td style="background-color: #FF0000; color: white;">Flammability</td> </tr> <tr> <td style="background-color: #FFFF00; text-align: center;">0</td> <td style="background-color: #FFFF00;">Reactivity</td> </tr> <tr> <td style="text-align: center;">B</td> <td>Personal protection</td> </tr> </table> <p style="text-align: center;">B = Safety glasses + Gloves</p>	3	Health	0	Flammability	0	Reactivity	B	Personal protection
3	Health								
0	Flammability								
0	Reactivity								
B	Personal protection								
<p style="text-align: center;">HMIS Protection Group B</p>	<div style="text-align: center;">  </div>								
<p>All pertinent hazard information has been provided in this SDS, per the requirements of the U.S. Federal Occupational Safety and Health Administration Standard (29 CFR 1910.1200), U.S. State equivalent Standards, and the Canadian Workplace Hazardous Materials Identification System Standards (CPR 4).</p>									

[Back to Top](#)

SECTION 16: OTHER INFORMATION

ACRONYM LIST

ACGIH	American Conference of Governmental Industrial Hygienists
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service
CFR	Code of Federal Regulations
DSL/NDSL	Domestic Substances List/ Non-domestic Substance List
EC₅₀	Half maximal effective concentration
HMIS	Hazardous Materials Identification System

PREPARED BY:

Regulatory Division
Project Clean Inc.
(formerly Maxim Chemical International Inc.)

LAST UPDATE:

2020-05-15

SECTION 16: OTHER INFORMATION	
IARC	International Agency for Research on Cancer
LC₅₀	Lethal concentration, 50%
LD₅₀	Lethal dose, 50%
MSHA	Mine Safety and Health Administration
N/A	Not Available
NIOSH	The National Institute for Occupational Safety and Health
N.O.S.	Not Otherwise Specified
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
PNOC	Particulates not otherwise classified
PMMCC	Pensky-Martens Closed Cup
P_{ow}	Partition Coefficient Octanol: Water
SDS	Safety Data Sheets
STOT – SE	Specific Target Organ Toxicity – Single Exposure
STOT – RE	Specific Target Organ Toxicity – Repeated Exposure
TDG	Transportation of Dangerous Goods
TLV	Threshold Limit Value
UN	United Nations
VOCs	Volatile Organic Compounds
WEL	Workplace Exposure Limit
WHMIS	Workplace Hazardous Materials Information System

[Back to Top](#)

It is the responsibility of the user to provide a safe workplace, using the health and safety information contained herein as a guide. Project Clean Inc. (formerly Maxim Chemical International Inc.) will accept no liability for damages or loss incurred from the improper handling and use of this product.

The information provided in the Safety Data Sheet has been obtained from current sources and is believed to be reliable.

PREPARED BY:

Regulatory Division
Project Clean Inc.
(formerly Maxim Chemical International Inc.)

LAST UPDATE:

2020-05-15