



CourtMaster

Specialized Wood Care Finish

DESCRIPTION

CourtMaster is the superstar of wood floor coatings. This unique, water-based urethane finish provides exceptional durability, appearance and protection. **CourtMaster** has reduced VOCs (Volatile Organic Compounds) compared with traditional solvent-based coatings.

DIRECTIONS

Screen and Recoat:

1. Remove all soil from the floor including gum, wax or adhesives.
2. Screen the floor with 80-100 grit screens. Sweep and vacuum all dust.
3. Make certain that air movement is reduced before tacking. Tack floor completely with damp toweling.
4. Make certain floor is dust-free. Allow floor to dry completely. All moisture must be gone.
5. Apply 1st coat of **CourtMaster** with a flow applicator, T Bar or wood block applicator. Allow 3-4 hours under normal conditions to dry.
6. Apply 2nd coat of **CourtMaster** within 4 hours after 1st coat has completely dried to the touch.

The floor will take light walking traffic after 24 hours and heavy traffic after 48 hours. For newly sanded floors, contact your Maxim Representative.

Scrub and Recoat:

1. Scrub floor using single speed swing floor machine with black floor pads using *MultiMax* at 2-4 oz. per gallon (1:32-1:64). Work an area of 200-400 sq.ft. (20-40 sq.m) at a time.
2. Vacuum immediately after scrubbing. Complete the remainder of the floor using the same procedures.
3. If using an autoscrubber, double scrub 400-800 sq.ft. (40-80 sq.m) at a time using *MultiMax* at 2-4 oz. per gallon (1:32-1:64). Rinse floor thoroughly with cold water. Allow floor to dry completely. All moisture must be gone.

Apply **CourtMaster** following the same procedure as in screen and recoat above.

PHYSICAL DATA

pH	7.5 – 8.5
Drying Time	3-4 hours per coat
Coverage	800-1200 ft.per gallon (20-30 m ² /L)
Slip Resistance	Passes ASTM D2047
Performance	Excellent Leveling, Scrubability and Durability

Durable. Reliable. Long lasting. Commercial floor finish.