



FLEX CLAD

Flexible Floor Coating

DESCRIPTION

Flex Clad is a special water-based coating/finish designed for use on resilient surfaces such as rubber flooring, sport mats, rubber mats and runners.

Flex Clad's a tough and flexible finish, formulated to protect and beautify rubber surfaces. **Flex Clad** provides great initial gloss and has excellent adhesion to these rubber surfaces. Having a finish on rubber surfaces improves ease of cleaning. **Flex Clad** is also easily strippable.

DIRECTIONS

Preparation

Vacuum all surfaces. Clean new surfaces with *NeutraMax* at 2 oz/US gallon (16 ml/L) (1:64) and rinse.

Deep scrub with *MultiMax* or strip previously coated surfaces with *#1 Remover* or *Burlesque*. Rinse well and allow to dry completely.

Application

Apply 2-3 thin to medium thickness coats of **Flex Clad** using a microfibre or string mop. Allow 35-45 minutes between each coat.

Apply additional coats (up to 3 maximum) to achieve desired gloss within a 24-hour period.

Maintenance

Dust mop or vacuum floor frequently. Damp mop with *NeutraMax* at 2oz/US gallon (16ml/L) (1:64) as needed to keep clean.

Buff as needed to maintain gloss. Care must be taken due to the unevenness of rubber floors.

PHYSICAL DATA

Solids	20% minimum
Drying Time	35-45 minutes
Coverage	2000 – 3000 sq.ft. / US gallon
Slip Resistance	Passes ASTM D2047
Color	White
Foam	Low
Odor	Sweet, solvent

Durable. Reliable. Long lasting. Commercial floor finish.