



HI-SHINE

Urethane-fortified Floor Finish

DESCRIPTION

Hi-Shine is an extremely durable floor finish designed to save time and money. **Hi-Shine** is a combination of urethane and polymers that deliver a rich, water clear gloss to bring out a floor's natural beauty without hiding under a thick, wax barrier.

Hi-Shine is a versatile floor finish that can be applied on a variety of floors such as linoleum, vinyl, vinyl asbestos, tile, marble, concrete, marmoleum and even sealed wood. It can be used alone or in conjunction with a high-quality sealer such as *Holdout®*, and can be applied directly on top of most other finishes. **Hi-Shine** readily responds to high speed burnishing, however some users simply top coat with a thin layer of **Hi-Shine** to forgo burnishing.

Hi-Shine is recommended for schools, restaurants and other high traffic areas that require great gloss and great durability. It does not yellow and can withstand high traffic wear and the abrasiveness of high speed burnishing equipment so your floor shines bright and clear for a long, long time.

DIRECTIONS

Preparation:

Strip the floor with #1 Remover then pick up spent solution with a mop or wet-vac making sure solution does not dry. Rinse floor with *NeutraMax* as per label instructions.

Application:

1. Use a clean finish mop, either fine string or candy striped. Pre-wet with water and wring out mop to conserve finish. 2. Apply 2-3 even coats of **Hi-Shine**. More may be required if you have an un-sealed, porous floor or need a good base to propane burnish. 3. Immerse mop in finish. Do not wring your mop but press firmly into wringer to remove excess finish.

Maintenance:

1. Dust floor with treated dust mop. 2. Clean floor by damp mopping or autoscrubber using Maxim's neutral detergent, *NeutraMax*, as per label instructions. 3. Spray buff with *Armor-Ace* or burnish as desired. *Armor-Ace* may be used to enhance the gloss by applying before burnishing. Or use a thin topcoat of **Hi-Shine** as necessary to restore your floor to its original, glossy shine.

Burnishing:

Those who burnish **Hi-Shine** generally use a medium synthetic pad - either champagne or aqua.

PHYSICAL DATA

Solids	20%
Drying Time	15-20 minutes
Coverage	3, 000 square feet per US gallon
Slip Resistance	Passes ASTM D2047
Performance	Excellent Leveling, Scrubability, Black Mark Resistance and Removability

Durable. Reliable. Long lasting. Commercial floor finish.