

### DESCRIPTION

**Nu Break 8** is used in cabinet spray re-circulation washers and hot tanks to remove carbon, oil, grease, paint and other contaminants. It is used by maintenance shops in railroads, pulp and paper mills, and mines. It is also used by machine shops, engine rebuild and transmission shops.

### FEATURES & BENEFITS

concentrated • highly alkaline • water soluble • non-flammable

### DIRECTIONS

Use **Nu Break 8** at 1-5 oz per US gallon of water (10-40 ml/litre) (1:100-1:25) depending on the amount of grease and oil residues. The most effective temperature range is 160 - 190°F (70 - 90°C).

### FIRST AID

**Eyes & Skin:** If eye or skin contact occurs, immediately flush with plenty of water for at least 15 minutes. Call a physician. **Inhalation:** Remove to fresh air. Call a physician. **Ingestion:** If swallowed, promptly give plenty of water or milk. Do not induce vomiting. Call a physician.

For further information, please review the **Safety Data Sheet (SDS)** and **Product Label**.

### STORAGE & HANDLING

Keep from freezing. Store upright in original closed container at room temperature away from children. Do not mix with any other chemicals.

Do not store in aluminum, copper, copper alloys and galvanized containers.

### PHYSICAL DATA

Package: 18.9L pails, 275  
Gallon drums, 55 Gallon kegs  
Appearance: clear liquid  
Colour: colourless  
Foam: low  
Odour: none  
pH: 12.5-13.5

### ProjectClean.com

1607 Derwent Way, Delta, BC, Canada V3M 6K8  
1-800-663-9925

### Product code:

1400980-18.9  
1400980-275gal  
1400980-55gal