



SheerGloss

sealer/finish

DESCRIPTION

SheerGloss was developed with everyone in mind. **SheerGloss'** smooth levelling and initial high gloss combined with excellent wearability and resistance to ultra high speed pad abrasion makes **SheerGloss** a natural choice for most maintenance procedures. Regardless of the maintenance program you have to deal with, **SheerGloss** looks good and keeps on working. The clear, long wearing film produced by **SheerGloss** will reduce yellowing and resist scuffing, resulting in less frequent stripping while extending the film life between re-coats. **SheerGloss** can be used on most types of resilient flooring such as linoleum, marmoleum, vinyl sheet and vinyl composite tile.

DIRECTIONS

A sealer is not required, but if you have a very porous floor it may be advantageous to apply *Foundation* or *Holdout*® sealer. Two coats are often sufficient.

Preparation:

Strip the floor with *#1 Remover* then pick up spent solution with a mop or wet vac making sure solution does not dry. Rinse floor with *NeutraMax* as per label instructions.

Application:

Use a clean finish mop, either fine string or candy striped. Pre-wet with water and wring out mop to conserve finish.

Apply 4-5 even coats of **SheerGloss**. More may be required if you have an un-sealed, porous floor or need a good base to propane burnish. Immerse mop in finish. Do not wring your mop but press firmly into wringer to remove excess finish.





SheerGloss

sealer/finish

Maintenance:

Dust floor with treated dust mop.

Clean floor by damp mopping or autoscrubber using M-chem neutral detergent, *NeutraMax*, as per label instructions.

Spray buff with *Armor Ace* or burnish as desired. *Armor Ace* may be used to enhance the gloss by applying before burnishing. Consult the *Armor Ace* label for detailed instructions.

PHYSICAL DATA

| | |
|-----------------|---|
| Solids | 20% minimum |
| Drying Time | 20-30 minutes |
| Coverage | 2500 Sq feet per gallon (average) |
| Slip Resistance | Passes ASTM D2047-82 |
| Performance | Excellent Leveling, Scrubability, Black mark Resistance and Removability. |

